

	DN25–DN50 CE
	DN65–DN150 CE
	DN200 CE

Working temperature -10 °C/+100 °C**Materials**

1	Body	Ductile Iron – EN-GJS-400-15 (GGG40)
2	Ball	Brass – CuZn40Pb2 (Ms 58)
3	Stem	Stainless Steel – X5CrNi18-10 (A304)
4	Seats	PTFE
5	O-Ring	NBR
6	Handle	Carbon Steel (Galvanised) – S235JR (RSt 37-2)

KPC DN ... PN16 DP NX PB**PN16**

Art. nr.	DN	A	ØB	C	ØD	G	b	ØDk	Ød	Nr.	Top flange ISO	Shaft ØSxP/K	Weight (kg)
A952063	25	125	115	76	25	150	18	85	14	4	F03	14x10	3,82
A952064	32	130	140	92	31	235	18	100	18	4	F04	17,6x12	5,53
A952065	40	140	150	97	39	235	18	110	18	4	F05	17,6x12	6,55
A952066	50	150	165	105	49	271	20	125	18	4	F05	17,6x12	8,65
A952067	65	170	185	124	63	288	18	145	18	4	F07	23,6x17	11,65
A952068	80	180	200	133	76	288	20	160	18	8	F07	23,6x17	13,80
A952069	100	190	220	153	100	288	20	180	18	8	F07	23,6x17	18,60
A952070	125	200	250	183	125	541	22	210	18	8	F10	31,6x19	29,50
A952049	125	325*	250	183	125	541	22	210	18	8	F10	31,6x19	29,50
A952071	150	210	285	203	150	541	22	240	22	8	F10	31,6x19	38,00
A952052	150	350*	285	203	150	541	22	240	22	8	F10	31,6x19	38,00
A952072	200	400*	340	316	200	1000	24	295	22	12	F12	K30	83,00

KPC DN ... PN40 DP NX PB**PN40**

Art. nr.	DN	A	ØB	C	ØD	G	b	ØDk	Ød	Nr.	Top flange ISO	Shaft ØSxP/K	Weight (kg)
A952063	25	125	115	76	25	150	18	85	14	4	F03	14x10	3,82
A952064	32	130	140	92	31	235	18	100	18	4	F04	17,6x12	5,53
A952065	40	140	150	97	39	235	18	110	18	4	F05	17,6x12	6,55
A952066	50	150	165	105	49	271	20	125	18	4	F05	17,6x12	8,65

Working temperature -10 °C/+150 °C**Materials**

1	Body	Ductile Iron – EN-GJS-400-15 (GGG40)
2	Ball	Brass – CuZn40Pb2 (Ms 58)
3	Stem	Stainless Steel – X5CrNi18-10 (A304)
4	Seats	PTFE
5	O-Ring	EPDM
6	Handle	Carbon Steel (Galvanised) – S235JR (RSt 37-2)

KPC DN ... PN16 DP EX PB**PN16**

Art. nr.	DN	A	ØB	C	ØD	G	b	ØDk	Ød	Nr.	Top flange ISO	Shaft ØSxP/K	Weight (kg)
A953013	25	125	115	76	25	150	18	85	14	4	F03	14x10	3,82
A953015	32	130	140	92	31	235	18	100	18	4	F04	17,6x12	5,53
A952017	40	140	150	97	39	235	18	110	18	4	F05	17,6x12	6,55
A952018	50	150	165	105	49	271	20	125	18	4	F05	17,6x12	8,65
A952019	65	170	185	124	63	288	18	145	18	4	F07	23,6x17	11,65
A952020	80	180	200	133	76	288	20	160	18	8	F07	23,6x17	13,80
A952021	100	190	220	153	100	288	20	180	18	8	F07	23,6x17	18,60
A952022	125	200	250	183	125	541	22	210	18	8	F10	31,6x19	29,50
A952050	125	325*	250	183	125	541	22	210	18	8	F10	31,6x19	29,50
A952023	150	210	285	203	150	541	22	240	22	8	F10	31,6x19	38,00
A952053	150	350*	285	203	150	541	22	240	22	8	F10	31,6x19	38,00
A952024	200	400*	340	316	200	1000	24	295	22	12	F12	K30	83,00

KPC DN ... PN40 DP EX PB**PN40**

Art. nr.	DN	A	ØB	C	ØD	G	b	ØDk	Ød	Nr.	Top flange ISO	Shaft ØSxP/K	Weight (kg)
A953013	25	125	115	76	25	150	18	85	14	4	F03	14x10	3,82
A953015	32	130	140	92	31	235	18	100	18	4	F04	17,6x12	5,53
A952017	40	140	150	97	39	235	18	110	18	4	F05	17,6x12	6,55
A952018	50	150	165	105	49	271	20	125	18	4	F05	17,6x12	8,65

Working temperature -10 °C/+180 °C

Materials

1	Body	Ductile Iron – EN-GJS-400-15 (GGG40)
2	Ball	Brass – CuZn40Pb2 (Ms 58)
3	Stem	Stainless Steel – X5CrNi18-10 (A304)
4	Seats	PTFE
5	O-Ring	PTFE
6	Handle	Carbon Steel (Galvanised) – S235JR (RSt 37-2)

KPC DN ... PN6 DP PX PB

PN6

Art. nr.	DN	A	ØB	C	ØD	G	b	ØDk	Ød/M**	Nr.	Top flange ISO	Shaft ØSxP/K	Weight (kg)
A952206	25	125	100	76	25	150	18	75	11/M10	4	F03	14x10	3,82
A952207	32	130	120	92	31	235	18	90	14/M12	4	F04	17,6x12	5,53
A952203	40	140	130	97	39	235	18	100	14/M12	4	F05	17,6x12	6,55
A952204	50	150	140	105	49	271	20	110	14/M12	4	F05	17,6x12	8,65
A952200	65	170	160	124	63	288	18	130	14	4	F07	23,6x17	11,65
A952201	80	180	190	133	76	288	20	150	18	4	F07	23,6x17	13,80
A952202	100	190	210	153	100	288	20	170	18	4	F07	23,6x17	18,60
A952205	125	200	240	183	125	541	22	200	M16	8	F10	31,6x19	29,50
A952208	150	210	265	203	150	541	22	225	M16	8	F10	31,6x19	38,00

Notes

**M – thread

KPC DN ... PN16 DP PX PB

PN16

Art. nr.	DN	A	ØB	C	ØD	G	b	ØDk	Ød	Nr.	Top flange ISO	Shaft ØSxP/K	Weight (kg)
A953014	25	125	115	76	25	150	18	85	14	4	F03	14x10	3,82
A953016	32	130	140	92	31	235	18	100	18	4	F04	17,6x12	5,53
A952029	40	140	150	97	39	235	18	110	18	4	F05	17,6x12	6,55
A952030	50	150	165	105	49	271	20	125	18	4	F05	17,6x12	8,65
A952031	65	170	185	124	63	288	18	145	18	4	F07	23,6x17	11,65
A952032	80	180	200	133	76	288	20	160	18	8	F07	23,6x17	13,80
A952033	100	190	220	153	100	288	20	180	18	8	F07	23,6x17	18,60
A952034	125	200	250	183	125	541	22	210	18	8	F10	31,6x19	29,50
A952051	125	325*	250	183	125	541	22	210	18	8	F10	31,6x19	29,50
A952035	150	210	285	203	150	541	22	240	22	8	F10	31,6x19	38,00
A952054	150	350*	285	203	150	541	22	240	22	8	F10	31,6x19	38,00
A952036	200	400*	340	316	200	1000	24	295	22	12	F12	K30	83,00

KPC DN ... PN40 DP PX PB

PN40

Art. nr.	DN	A	ØB	C	ØD	G	b	ØDk	Ød	Nr.	Top flange ISO	Shaft ØSxP/K	Weight (kg)
A953014	25	125	115	76	25	150	18	85	14	4	F03	14x10	3,82
A953016	32	130	140	92	31	235	18	100	18	4	F04	17,6x12	5,53
A952029	40	140	150	97	39	235	18	110	18	4	F05	17,6x12	6,55
A952030	50	150	165	105	49	271	20	125	18	4	F05	17,6x12	8,65